

P Series Non-Articulating Borescopes



**NOW WITH A TUNGSTEN
BRIAAD SHEATHING FOR
BETTER DURABILITY**

The P Series flexible borescope features a small diameter with high magnification and high resolution 10,000 element imaging bundle for straight-forward or right-angle viewing. It is non-articulating, but offers several performance features for versatile use. The P Series borescope is video adaptable with fibreoptic illumination.

Features & Specifications

Diameter: 0.125" (3.18mm)
 Flexible Length: 24" (610mm) & 36" (914.4mm)
 Minimum Bend Radius: 1.5" (38mm)
 Illumination: 1 Watt LED Battery Flashlight handle included at no extra cost.
 Magnification: 25X
 Field of View: 55°
 Focal Length: 0.2" to 3" (5mm to 75mm)
 Maximum Temperature: 257°F (125°C)
 Other Features: Straight-forward viewing
 Tungsten Braid Sheathing
 Carrying case

Accessories & Options

- P-90 Viewing Head Adapter for 90° right-angle viewing
- FOI-150 Fibreoptic Illuminator with 150W quartz halogen lamp
- FB-6 Fibre Bundle to connect fibreoptic illuminator to the borescope
- TSVD-30 Video Adapter
- **USA made quality instrument**

P Series Ordering Information

Model Number	Flexible Length
P-O-24	24" (610mm)
P-O-36	36" (914.4mm)
Accessories & Options	
P-90	90 Deg. Mirror Tip
FOI-150	150 Watt Halogen Illuminator
FB-6	Fiber Optic Light Guide
TSVD-30	C Mount Video Adater