

## TR.L1 16 LED RING ILLUMINATOR

The Titan Tool Supply, Inc. new TR.L1 16 Led Ring Illuminator is designed for use with the Titan CS Centering Microscopes & Modular Toolscopes has the following characteristics.

\* Homogeneous lighting throughout the entire work area.

\* Perfect incident light illumination for applications with cameras and lenses in industrial image processing.

\* Flicker-free light thanks to optimized, low-loss electronics.

\* Brightness adjustable from 0 - 100%, with pure white (6500 K) illumination.

\* Variable clamping diameter, adjustable with reducing ring.

\* Robust aluminum housing in a modern design.

## **Specifications:**

360° Shadow-free Illumination
16LED Life: 50,000 Hrs. approximately
6500° K pure white color spectrum
Anodized Aluminum housing
3 point mount ring for secure mounting M21 X 0.75

Ring Dimensions: OD 1.73" (44mm), ID 0.78" (20mm) H 0.984" (25mm) Weight of Ring: 2 oz. (60g) approx. Length of Power Cord to Ring: 33" (0.85m) Working distance 0.197" - 0.985" (5mm to 25mm)

Integrated Controller:

- Adjustable brightness (0-100% with memory function)
- Output Power: 24V DC 1A Power consumption 4W
- Universal power Input 100-240VAC 50/60Hz with US, EU & UK power plugs.

- Power Supply Dimensions: 3" (78mm) X 1.5" (38mm) X 0.825" (21mm)

Length of Controller Power Cable 55" (1.4m)





## TR.L1 LED Ordering Information

Order Number	Illumination	
TR.L1	16 LED Ring Illuminator	
TR.L1.18RR	26MM to 18MM Reducer Ring	

## www.TitanToolSupply.com • Phone: 716-873-9907



Titan Tool Supply, Inc. • 68 Comet Avenue, Buffalo NY 14216 Phone: 716-873-9907 • Fax: 716-873-9998 • E-mail: info@titantoolsupply.com • www.TitanToolSupply.com